OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER Wilcoxen PARTY CHIEF: ____ CREW: _ TYPE OF MARKER: Harrison (no cap '04) METHOD OF ESTABLISHMENT: ____County: 11-16-98 ount IN. S.P.C. E ZONE NAD NAME: 15050302 503416.5890(m) N: 74704.7390(m) E : 37.52 30.19 10th Street 1000 N 3.

10th St. 1000 N

There is no reference per original survey by Hendricks 1820 Marion County Atlas pg. 14. Hosbrook 1/20 & 21-1853 called following witness: 9" sugar maple N 25 W 23 links, 14" beech S 31 E 44 links per Warren Township Legal Survey Book pg. 16. Coyner 5-1-1900 called stone found per Warren Township Legal Survey Book pg. 61. Reference (no date) called pipe over stone 18" down. 12-27-74 called PK nail over pipe over stone. Excavated 10-20-86 MCSO called railroad spike w/ cut 'x' fd. at surface, over 1" pipe over stone 12" down; also, 1" pipe found beside stone. Harrison set. 10-20-86. Re-tied 11-16-98 by Wilcoxen. Re-tied 5-11-04 by Wilcoxen.

15050302		
REF.	DISTANCE	DESCRIPTION
1.	30.19	Due E to S Q 34-16-5 Harrison
2.	74.03'	PK nail N PwP#114521 E 12"up
3.	30.06	PK nail W PwP#241-521 E 3"up
4.	38.28'	Cut 'x' NW bolt of street light base
5.	87.39	Top nut of fire hydrant
6.	37.52'	Due W to C/L of Woodlark (PK nail)
7.	24.27	Cut 'x' SW metal plate PwP#240-521 E A
11		